Panasonic



42-inch Class FULL HD LCD Display

TH-42LF30U


Screen Size (Diagonal)	42.0-inch (1067 mm)	
Aspect ratio	16:9	
Effective Display Area (W x H)	36.6" x 20.6" (930 x 523 mm)	
Number of pixels (H x V)	1920 x 1080 pixels	
Brightness (Typ)	700 cd/m²	
Contrast Ratio	1200:1	
Response Time	9 ms (G to G)	
Viewing Angle (Horizontal/Vertical)	178° /178°	
Operating Life	approx. 50,000 hours*	
*An approximate time until the panel brig CONNECTION TERMINAL	htness decreases to half of its original value.	
VIDEO IN	BNC x 1	1.0 Vp-p (75Ω)
AUDIO IN (L/R)	RCA Pin jack x 1 set	0.5 Vrms
COMPONENT/RGB IN	BNC x 3	G/Y : with sync 1.0 Vp-p (75Ω)
		B/P _B /C _B : 0.7 Vp-p (75Ω)
		R/P _R /C _R : 0.7 Vp-p (75Ω)
AUDIO IN (L/R)	RCA Pin jack x 1 set	0.5 Vrms
HDMI IN	HDMI TYPE A x 2	
DVI-D IN	DVI-D 24 Pin x 1	Compliance with DVI Revision 1.0
	Content Protection	Compatible with HDCP 1.1
AUDIO IN (L/R)	Stereo mini jack (M3) × 1	0.5 Vrms (Shared with PC IN)
DVI-D OUT	DVI-D 24pin x 1	Compliance with DVI Revision 1.0
PC IN	Mini D-sub 15 Pin x1	G : with sync 1.0 Vp-p (75Ω)
	Plug & Play (VESA DDC 2B)	: without sync 0.7 Vp-p (75 Ω)
		B : 0.7 Vp-p (75Ω)
		R : 0.7 Vp-p (75Ω)
		HD/VD : 1.0 - 5.0 Vp-p (high impedance)
AUDIO IN (L/R)	Stereo mini jack (M3) \times 1	0.5 Vrms (Shared with DVI-D IN)
SLOT2.0	Yes	
SERIAL	D-SUB 9 pin x 1 (SERIAL IN)/D-SUB 9 pin x 1	1 (SERIAL OUT) RS-232C Compatible
LECTRICAL		
Power Requirements	110-127V AC, 50Hz/60Hz	
Rated Power Consumption	300W	
On Mode Average Power Consumption*	approx. 199W	
Power off condition	0.3W	
Stand-by condition	0.5W	
*Based on IEC 62087 Ed.2 measurement	method.	
AUDIO		
Built-in Speakers	8Ω, 10W [5W + 5W] (10%THD)	
MECHANICAL		
Dimensions (W x H x D)	38.2" x 22.1" x 4.6" (968 x 561 x 116 mm)	
Carton Dimensions (W x H x D)	43.4" x 27.9" x 8.9" (1101 x 707 x 224 mm)	
Weight	approx. 46.3 lbs. (21.0 kg)	
Gross weight	approx. 57.4 lbs. (26.0 kg)	
Bezel Width	0.72" (18.3 mm)	
Cabinet Material / Color	Plastic / Black	
VESA mount	VESA 15.8" x 15.8" (400 x 400 mm)	
NVIRONMENTAL		
Operating environment	Temperature : 32°F to 104°F (0°C to 40)℃)
	Humidity : 20% to 80% (Non con	ndensation)
Storage environment	Temperature : -4°F to 140°F (-20°C to 6	50℃)*
	Humidity : 20% to 90% (Non cond	densation)
	C to 60° C), please keep in humidity 20% to 40%.	
TANDARD (CERTIFICATIONS)		
SAFETY REGULATIONS	UL60065, CAN/CSA-22.2No60065:03	
RADIATION REGULATIONS	FCC Part 15 Class-B, ICES-003	
Energy Star Displays 5.1	Yes	
REMOTE CONTROL TRANSMITTER		
Power Requirements	DC 3V (2 x AA Size batteries)	
Operation distance	approx. 23 ft (7m) in front of display	
Weight	approx. 3.5 oz (100g) including batteries	

MAIN FEATURE

Digital Zoom	Yes (x1~x4)		
Video Wall	Yes (N x M, up to 5 x 5)		
Power-on Screen Delay	Yes		
Seam Hides Video Off Mode	Yes		
Daisy Chain	Yes		
1:1 Pixel mode	Yes		
Automatic Picture Position	Yes		
Screen Saver	Yes		
No signal power off	Yes		
PC Power Management	Yes		
DVI-D Power Management	Yes		
ECO mode	Yes		
Input lock	Yes		
Button lock	Yes		
Remote-control User Level	Yes		
Failover input	Yes		
Orientation	Landscape / Portrait		

OPTIONAL ACCESSORIES

Pedestal	TY-ST20-K		
HD-SDI Terminal Board	TY-FB10HD		



OCONNECTION TERMINAL



APPLICABLE INPUT SIGNALS

	Signal name	Horizontal frequency (kHz)	Vertical frequency (kHz)	VIDEO IN	COMPONENT IN (Dotdock(MHz))	RGB IN (Dotclock(MHz))	PC IN (Dotclock(MHz))	DVI-D IN (Dotdock(MHz))	HDMI1 HDMI2
SE SE	NTSC PAL	15.73 15.63	59.94 50.00	Y					
Signals	PAL 60	15.73	59.94	Y					
ဂ္ဂ	NTSC 4. 43	15.63 15.73	50.00 59.94	Y					
Video	PAL M	15.73 15.63	59.94 50.00	Y					
	525(480)/60i 525(480)/60p	15.73 31.47	59.94 59.94		Y (13.5) Y (27.0)			Y (27.0) Y (27.0)	Y
	625(575)/50i	15.63	50.00		Y (13.5)			` '	
Jais	625(576)/50i 625(575)/50p	15.63 31.25	50.00 50.00		Y (27.0)			Y (27.0)	Y
Signal	625(576)/50p 750(720)/60p	31.25 45.00	50.00 60.00		Y (74.25)			Y (27.0) Y (74.25)	Y Y
Component	750(720)/50p 1125(1080)/60p	37.50 67.50	50.00 60.00		Y (74.25) Y (148.5)*1			Y (74.25) Y (148.5)	Y Y
	1125(1080)/60i 1125(1080)/50p	33.75 56.25	60.00 50.00		Y (74.25)*1 Y (148.5)*1			Y (74.25)	Y Y
Ę	1125(1080)/50i	28.13	50.00		Y (74.25)*1			Y (148.5) Y (74.25)	Y
١	1125(1080)/24sF 1125(1080)/30p	27.00 33.75	48.00 30.00		Y (74.25)*2 Y (74.25)*1			Y (74.25)	Υ
ŀ	1125(1080)/25p 1125(1080)/24p	28.13 27.00	25.00 24.00		Y (74.25)*1 Y (74.25)*1			Y (74.25) Y (74.25)	Y Y
	640x400@70Hz 640x400@85Hz	31.46 37.86	24.00 70.07 85.08		. (*==/	Y (25.17) Y (31.5)	Y (25.17) Y (31.5)	Y (25.17) Y (31.5)	
	640x480@60Hz	31.43	59.88			Y (25.15)	Y (25.15)	Y (25.15)	.,
	640x480@60Hz 640x480@67Hz	31.47 35.00	59.94 66.67			Y (25.18) Y (30.24)	Y (25.18) Y (30.24)	Y (25.18) Y (30.24)	Y
ŀ	640x480@72Hz 640x480@75Hz	37.86 37.50	72.81 75.00			Y (31.5) Y (31.5)	Y (31.5) Y (31.5)	Y (31.5) Y (31.5)	
İ	640x480@85Hz 720x400@70Hz	43.27 31.47	85.01 70.08			Y (36.0) Y (28.32)	Y (36.0) Y (28.32)	Y (36.0) Y (28.32)	
	800x600@55Hz	34.50	55.38			Y (35.33)	Y (35.33)	Y (35.33)	
	800x600@56Hz 800x600@60Hz	35.16 37.88	56.25 60.32			Y (36.0) Y (40.0)	Y (36.0) Y (40.0)	Y (36.0) Y (40.0)	Υ
ł	800x600@60Hz 800x600@72Hz	38.00 48.08	60.51 72.19			Y (40.13) Y (50.0)	Y (40.13) Y (50.0)	Y (40.13) Y (50.0)	
	800x600@75Hz 800x600@85Hz	46.88 53.67	75.00 85.06			Y (49.5) Y (56.25)	Y (49.5) Y (56.25)	Y (49.5) Y (56.25)	
	852x480@60Hz 1024x768@50Hz	31.47 39.55	59.94 50.00			Y (33.54) Y (51.89)	Y (33.54) Y (51.89)	Y (34.24) Y (51.89)	Y
	1024x768@60Hz	48.36	60.00			Y (65.0)	Y (65.0)	Y (65.0)	Y
	1024x768@60Hz 1024x768@70Hz	48.50 56.48	60.02 70.07			Y (64.99) Y (75.0)	Y (64.99) Y (75.0)	Y (65.18) Y (75.0)	
	1024x768@75Hz 1024x768@75Hz	60.24 60.02	74.93 75.03			Y (80.0) Y (78.75)	Y (80.0) Y (78.75)	Y (80.0) Y (78.75)	
Ì	1024x768@75Hz 1024x768@85Hz	61.01 68.68	75.70 85.00			Y (80.05) Y (94.5)	Y (80.05) Y (94.5)	Y (81.0) Y (94.5)	
₽ B	1024x768@120Hz	97.55	119.99				Y (115.5)	Y (115.5)	
olgrid	1066x600@60Hz 1152x864@60Hz	37.64 53.70	59.94 60.00			Y (53.0) Y (81.62)	Y (53.0) Y (81.62)	Y (53.0) Y (81.62)	Y Y
اخ	1152x864@75Hz 1152x900@65Hz	67.50 61.20	75.00 65.20			Y (108.0) Y (92.0)	Y (108.0) Y (92.0)	Y (108.0) Y (92.0)	
ł	1152x900@66Hz 1152x900@75Hz	61.85 71.40	66.00 75.60			Y (94.5) Y (105.1)	Y (94.5) Y (105.1)	Y (94.5) Y (105.1)	
	1280x768@60Hz 1280x800@50Hz	47.78 41.20	59.87 50.00			Y (79.50) Y (68.55)	Y (79.50) Y (68.55)	Y (79.50) Y (68.55)	
	1280x960@60Hz 1280x960@85Hz	60.00 85.94	60.00 85.00			Y (108.0) Y (148.5)	Y (108.0) Y (148.5)	Y (108.0)	
Ì	1280x1024@50Hz	52.70	50.00			Y (89.38)	Y (89.38)	Y (148.5) Y (89.38)	Υ
ł	1280x1024@60Hz 1280x1024@60Hz	63.34 63.90	59.98 60.00			Y (108.18) Y (107.35)	Y (108.18) Y (107.35)	Y (108.18) Y (107.35)	
-	1280x1024@60Hz 1280x1024@60Hz	63.37 63.74	60.01 60.02			Y (107.5) Y (108.1)	Y (107.5) Y (108.1)	Y (107.5) Y (108.1)	
	1280x1024@60Hz 1280x1024@60Hz	63.98 63.79	60.02 60.18			Y (108.0) Y (108.19)	Y (108.0) Y (108.19)	Y (108.0) Y (108.19)	Υ
	1280x1024@66Hz	70.66	66.47			Y (119.84)	Y (119.84)	Y (119.84)	
	1280x1024@75Hz 1280x1024@76Hz	79.98 81.13	75.02 76.11			Y (135.0) Y (135.0)	Y (135.0) Y (135.0)	Y (135.0) Y (135.0)	
	1280x1024@85Hz 1360x768@60Hz	91.15 47.71	85.02 60.02			Y (85.5)	Y (157.5) Y (85.5)	Y (157.5) Y (85.5)	
	1366x768@50Hz 1366x768@60Hz	39.55 48.36	50.00 60.00			Y (69.92) Y (86.71)	Y (69.92) Y (86.71)	Y (69.92) Y (87.44)	
-	1400x1050@60Hz 1400x1050@60Hz	65.12 65.32	59.91 59.98			Y (121.38) Y (121.75)	Y (121.38) Y (121.75)	Y (122.43) Y (121.75)	Y
	1400x1050@60Hz	65.35	60.12			Y (121.81)	Y (121.81)	Y (121.85)	
	1400x1050@75Hz 1600x1200@60Hz	82.28 75.00	74.87 60.00			Y (156.0) Y (162.0)	Y (156.0) Y (162.0)	Y (156.0) Y (162.0)	Y
	1920x1080@60Hz 1920x1200@60Hz	67.50 74.04	60.00 59.95			Y (148.5)	Y (148.5) Y (154.0)	Y (148.5) Y (154.0)	Y
	Macintosh13"(640x480) MacintoshLC13"(640x480)	35.00 34.97	66.67 66.60			Y (30.24) Y (31.33)	Y (30.24) Y (31.33)	Y (30.24) Y (31.33)	
ļ	Macintosh16"(832x624)	49.72	74.55			Y (57.28)	Y (57.28)	Y (57.28)	
- [Macintosh19"(1024x768) Macintosh21"(1152x870)	60.24 68.68	75.08 75.06			Y (80.0) Y (100.0)	Y (80.0) Y (100.0)	Y (80.0) Y (100.0)	

^{*1:}Based on SMPTE 274M standard. *2:Based on SMPTE RP211 standard.